

Spectral

General and technical information.

- Iris is available in two different sizes: 370 and 600 mm
- surface, pendant, wall and recessed (recessed in 370 mm only)
- light colors monochrome 3000 K, 4000 K and dynamic white from 2700 6500 K (DT8)
- low glare radial optical prism is integrated into the housing
- up to 5,000 lm (Iris 370 mm) and up to 11,000 lm (Iris-L 600 mm)
- two suspension and feed options either via near invisible three-wat split power cables (...- P) or via stainless steel cables (...- PS)
- magnetic cover to canopy for simple installation and maintenance access
- like the human eye, the Iris comes in different colors these accents are created by foils on the side







Spectral®

Transparent technology: Iris with radial prism


- pendant version with transparent power wire (...- P) or steel cables (...-PS)
- surface-mounted and recessed versions
- wall mounted version with opal housing
- highly efficient with up to 140 lm / W
- glare-limited up to $UGR_{REF}(4H/8H) < 19$
- opal variant (...- O) available













Spectral®

Scalable solutions to suit larger spaces: Iris-L 600 mm

- impressive output
 with up to 11,000 lm
 luminous flux direct /
 indirect
- highly efficient with up to 136 lm / W
- glare-limited up to $UGR_{REF}(4H/8H) < 19$
- as a pendulum version with transparent power wire (...- P) or steel cables (...- PS)










Spectral®

Iris-L surface mounted luminaire

 clear PMMA creates a floating impression on any wall or ceiling







Spectral[®]

Bend the rules for unique lighting solutions.

Spectral. Eine Marke der RIDI GROUP.

RIDI Leuchten GmbH Hauptstraße 31 - 33 72417 Jungingen

Tel.: + 49 7477 872 - 0

Fax.: + 49 7477 872 - 48 info@spectral-lighting.com www.spectral-lighting.com

Front page: © Liudmila Dutko - stock.adobe.com

