

- +44 (0) 1279 450882
- ⊕ WWW.RIDI-GROUP.CO.UK
- SALES@RIDI.CO.UK

Luminaire type


Product reference: IL4-WS-1132-830M-DAD-MP-FGED

Article Number: 97-IL400021ED
Product type: Pendant
Mounting type: Pendant

Applications: Office, General and Retail

Specification text


Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 2055lm with an efficacy of 105lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1132 x W40 x H62mm. Finished in Grey.



Lighting performance

Output lumens: 2055 lm 105 lm/W Efficacy: Rated power: 19.5 W Control gear: DALI Dimming range: 1-100% DC Suitable: Yes 3000K K Colour temperature: MacAdams < 3 CRI: 85 Radiation pattern: Symmetrical

Radiation pattern: Symmetric
Beam angle: Wide
Unified glare rating (U.G.R): 19



Physical details

 Finish:
 Grey

 Length:
 1132 mm

 Width:
 40 mm

 Height:
 62 mm

 IP Rating:
 IP20





