

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

## Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL4-WS-1132-840M-DAD-MP-FWES 97-IL400025ES Pendant Pendant Office, General and Retail

## Specification text

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 2119lm with an efficacy of 109lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1132 x W40 x H62mm. Finished in White.




## Lighting performance

Output lumens:	2119 lm
Efficacy:	109 lm/W
Rated power:	19.5 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	19

## Physical details

Finish:	White
Length:	1132 mm
Width:	40 mm
Height:	62 mm
IP Rating:	IP20





lightworks

**RIDI** GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.