

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL4-WS-1132-830M-DAD-OP-FWED 97-IL400028ED Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 2384lm with an efficacy of 122lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1132 x W40 x H62mm. Finished in White.




Lighting performance

.384 lm
22 lm/W
9.5 W
DALI
-100%
′es
000K K
: 3
35
symmetrical
Vide
22

Physical details

Finish:	White
Length:	1132 mm
Width:	40 mm
Height:	62 mm
IP Rating:	IP20







RIDI GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.