

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

## Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL4-S-1132-830M-DAD-MP-FBE 97-IL400038E Surface Mount Surface Office, General and Retail

#### Specification text

Surface Mount luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 2055lm with an efficacy of 105lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1132 x W40 x H62mm. Finished in Black.




## Lighting performance

| Output lumens:                | 2055 lm     |
|-------------------------------|-------------|
| Efficacy:                     | 105 lm/W    |
| Rated power:                  | 19.5 W      |
| Control gear:                 | DALI        |
| Dimming range:                | 1-100%      |
| DC Suitable:                  | Yes         |
| Colour temperature:           | 3000K K     |
| MacAdams                      | < 3         |
| CRI:                          | 85          |
| Radiation pattern:            | Symmetrical |
| Beam angle:                   | Wide        |
| Unified glare rating (U.G.R): | 19          |

#### Physical details

| Finish:    | Black   |
|------------|---------|
| Length:    | 1132 mm |
| Width:     | 40 mm   |
| Height:    | 62 mm   |
| IP Rating: | IP20    |
|            |         |





# lightworks

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.

**RIDI** GROUP UK