

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL4-S-1132-830M-DAD-OP-FBE 97-IL400047E Surface Mount Surface Office, General and Retail

Specification text

Surface Mount luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 2384lm with an efficacy of 122lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1132 x W40 x H62mm. Finished in Black.




Lighting performance

A	
Output lumens:	2384 lm
Efficacy:	122 lm/W
Rated power:	19.5 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	22

Physical details

Finish:	Black
Length:	1132 mm
Width:	40 mm
Height:	62 mm
IP Rating:	IP20





lightworks

RIDI GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.