

- +44 (0) 1279 450882
- ⊕ WWW.RIDI-GROUP.CO.UK
- SALES@RIDI.CO.UK

Luminaire type

Product reference: IL4-S-1132-840M-DAD-OP-FGE

Article Number: 97-IL400054E
Product type: Surface Mount
Mounting type: Surface

Applications: Office, General and Retail

Specification text


Surface Mount luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 2458lm with an efficacy of 126lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1132 x W40 x H62mm. Finished in Grey.



Lighting performance

Output lumens: 2458 lm 126 lm/W Efficacy: Rated power: 19.5 W Control gear: DALI Dimming range: 1-100% DC Suitable: Yes 4000KK Colour temperature: MacAdams < 3 CRI: 85 Radiation pattern: Symmetrical

Radiation pattern: Symmetrics
Beam angle: Wide
Unified glare rating (U.G.R): 22



Physical details

 Finish:
 Grey

 Length:
 1132 mm

 Width:
 40 mm

 Height:
 62 mm

 IP Rating:
 IP20





