

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

| Product reference: |
|--------------------|
| Article Number: |
| Product type: |
| Mounting type: |
| Applications: |

IL6-R-1137-840M-DAD-MP-FW 97-IL400123 Recessed Recessed Office, General and Retail

Specification text

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 2119Im with an efficacy of 109Im/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1137 x W54 x H85mm. Finished in White.




Lighting performance

| Output lumens: | 2119 lm |
|-------------------------------|-------------|
| Efficacy: | 109 lm/W |
| Rated power: | 19.5 W |
| Control gear: | DALI |
| Dimming range: | 1-100% |
| DC Suitable: | Yes |
| Colour temperature: | 4000K K |
| MacAdams | < 3 |
| CRI: | 85 |
| Radiation pattern: | Symmetrical |
| Beam angle: | Wide |
| Unified glare rating (U.G.R): | 19 |

Physical details

| Finish: | White |
|------------|---------|
| Length: | 1137 mm |
| Width: | 54 mm |
| Height: | 85 mm |
| IP Rating: | IP20 |
| | |





lightworks

RIDI GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.