

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL6-R-1137-830M-DAD-OP-FWE 97-IL400126E Recessed Recessed Office, General and Retail

Specification text

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 2384lm with an efficacy of 122lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1137 x W54 x H85mm. Finished in White.




Lighting performance

22041
2384 lm
122 lm/W
19.5 W
DALI
1-100%
Yes
3000K K
< 3
85
Symmetrical
Wide
22

Physical details

Finish:	White
Length:	1137 mm
Width:	54 mm
Height:	85 mm
IP Rating:	IP20





lightworks

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.

RIDI GROUP UK