

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

## Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL4-S-1482-840M-DAD-MP-FB 97-IL400244 Surface Mount Surface Office, General and Retail

## Specification text

Surface Mount luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 2774Im with an efficacy of 108Im/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1482 x W40 x H62mm. Finished in Black.




# Lighting performance

| 2774 lm     |
|-------------|
| 2774111     |
| 108 lm/W    |
| 25.7 W      |
| DALI        |
| 1-100%      |
| Yes         |
| 4000K K     |
| < 3         |
| 85          |
| Symmetrical |
| Wide        |
| 19          |
|             |

#### Physical details

| Finish:    | Black   |
|------------|---------|
| Length:    | 1482 mm |
| Width:     | 40 mm   |
| Height:    | 62 mm   |
| IP Rating: | IP20    |
|            |         |





# lightworks

**RIDI** GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.