

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK


SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-R-1487-830M-DAD-MP-FBES 97-IL400321ES Recessed Recessed Office, General and Retail

Specification text

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 26911m with an efficacy of 1051m/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1487 x W54 x H85mm. Finished in Black.



Lighting performance

Output lumens:	2691 lm
Efficacy:	105 lm/W
Rated power:	25.7 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	19

Physical details

Finish:	Black
Length:	1487 mm
Width:	54 mm
Height:	85 mm
IP Rating:	IP20





RIDI GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.

