iline 4

RIDI GROUP UK

+44 (0) 1279 450882
WWW.RIDI-GROUP.CO.UK
SALES@RIDI.CO.UK

Luminaire type

Product reference:	IL6-R-1487-840M-DAD-MP-FB
Article Number:	97-IL400324
Product type:	Recessed
Mounting type:	Recessed
Applications:	Office, General and Retail



Specification text

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 2774lm with an efficacy of 108lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1487 x W54 x H85mm. Finished in Black.

Lighting performance

Output lumens:	2774 lm
Efficacy:	108 lm/W
Rated power:	25.7 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	19



Physical details

Finish:	Black
Length:	1487 mm
Width:	54 mm
Height:	85 mm
IP Rating:	IP20

lightworks

RIDI GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes.
© 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.