

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

## Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL5-WS-1990-840M-DADI-MP-FBED 97-IL400408ED Pendant Pendant Office, General and Retail

## **Specification text**

Pendant luminaire from the iline 5 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 10593Im with an efficacy of 117Im/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1990 x W49 x H85mm. Finished in Black.




## Lighting performance


| Output lumens:                | 10593 lm    |
|-------------------------------|-------------|
| Efficacy:                     | 117 lm/W    |
| Rated power:                  | 90.8 W      |
| Control gear:                 | DALI        |
| Dimming range:                | 1-100%      |
| DC Suitable:                  | Yes         |
| Colour temperature:           | 4000K K     |
| MacAdams                      | < 3         |
| CRI:                          | 85          |
| Radiation pattern:            | Symmetrical |
| Beam angle:                   | Wide        |
| Unified glare rating (U.G.R): | <19         |

## Physical details

| Finish:    |  |  |
|------------|--|--|
| Length:    |  |  |
| Width:     |  |  |
| Height:    |  |  |
| IP Rating: |  |  |
|            |  |  |



Black 1990 mm 49 mm 85 mm IP20





**RIDI** GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.