

- +44 (0) 1279 450882
- WWW.RIDI-GROUP.CO.UK
- SALES@RIDI.CO.UK


## Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications:

IL4-WS-1972-830M-DADI-OP-FG 97-IL400412 Pendant Pendant Office, General and Retail

## **Specification text**

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 5997Im with an efficacy of 122Im/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear. Nominal dimensions L1972 x W40 x H62mm. Finished in Grey.




## Lighting performance

Output lumens:	5997 lm
Efficacy:	122 lm/W
Rated power:	49.1 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	22

## Physical details

Finish:	Grey
Length:	1972 mm
Width:	40 mm
Height:	62 mm
IP Rating:	IP20







**RIDI** GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.