

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

## Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL4-WS-1972-840M-DADI-OP-FWES 97-IL400416ES Pendant Pendant Office, General and Retail

## Specification text

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 61821m with an efficacy of 1261m/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1972 x W40 x H62mm. Finished in White.




## Lighting performance

Output lung and a	(102
Output lumens:	6182 lm
Efficacy:	126 lm/W
Rated power:	49.1 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	22

## Physical details

Finish:	White
Length:	1972 mm
Width:	40 mm
Height:	62 mm
IP Rating:	IP20







**RIDI** GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.