

- +44 (0) 1279 450882
- WWW.RIDI-GROUP.CO.UK
- SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL4-W5-1972-840M-DADI-OP-FBED 97-IL400417ED Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 61821m with an efficacy of 1261m/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1972 x W40 x H62mm. Finished in Black.




Lighting performance

Output lumens:	6182 lm
Efficacy:	126 lm/W
Rated power:	49.1 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	22

Physical details

Finish:	Black
Length:	1972 mm
Width:	40 mm
Height:	62 mm
IP Rating:	IP20







The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.

RIDI GROUP UK