

- +44 (0) 1279 450882
- WWW.RIDI-GROUP.CO.UK
- SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications:

IL4-WS-1972-830M-DAD-MP-FGES 97-IL400421ES Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 3581lm with an efficacy of 105lm/W. Light source colour temperature 3000KK and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1972 x W40 x H62mm. Finished in Grey.




Lighting performance

Output lumens:	3581 lm
Efficacy:	105 lm/W
Rated power:	34.1 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	19

Physical details

Finish:	Grey
Length:	1972 mm
Width:	40 mm
Height:	62 mm
IP Rating:	IP20





lightworks

RIDI GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.