

- +44 (0) 1279 450882
- WWW.RIDI-GROUP.CO.UK
- SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL4-WS-1972-840M-DAD-OP-FBED 97-IL400435ED Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 22. Light output of 4282lm with an efficacy of 126lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1972 x W40 x H62mm. Finished in Black.




Lighting performance

Output lumens:	4282 lm
Efficacy:	126 lm/W
Rated power:	34.1 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	22

Physical details

Finish:	Black
Length:	1972 mm
Width:	40 mm
Height:	62 mm
IP Rating:	IP20







RIDI GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.