

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL4-S-1972-840M-DAD-MP-FWED 97-IL400443ED Surface Mount Surface Office, General and Retail

Specification text

Surface Mount luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 3692lm with an efficacy of 108lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1972 x W40 x H62mm. Finished in White.




Lighting performance

Output lumens:	3692 lm
Efficacy:	108 lm/W
Rated power:	34.1 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	19

Physical details

Finish:	White
Length:	1972 mm
Width:	40 mm
Height:	62 mm
IP Rating:	IP20





lightworks

RIDI GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.