

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

## Luminaire type

Product reference:
Article Number:
Product type:
Mounting type:
Applications:

IL6-R-1977-840M-DAD-MP-FWE 97-IL400523E Recessed Recessed Office, General and Retail

## **Specification text**

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 3692lm with an efficacy of 108lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1977 x W54 x H85mm. Finished in White.



Output lumens:	3692 lm
Efficacy:	108 lm/W
Rated power:	34.1 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	19

## Physical details

Finish:	White
Length:	1977 mm
Width:	54 mm
Height:	85 mm
IP Rating:	IP20





**RIDI** GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.

