iline 4

RIDI GROUP UK

+44 (0) 1279 450882
WWW.RIDI-GROUP.CO.UK
SALES@RIDI.CO.UK

Luminaire type

Product reference:	IL6-R-1977-840M-DAD-MP-FGED
Article Number:	97-IL400525ED
Product type:	Recessed
Mounting type:	Recessed
Applications:	Office, General and Retail



Specification text

Recessed luminaire from the iline 4 family. Symmetrical, Wide lighting distribution, UGR 19. Light output of 3692lm with an efficacy of 108lm/W. Light source colour temperature 4000KK and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1977 x W54 x H85mm. Finished in Grey.

Lighting performance

Output lumens:	3692 lm
Efficacy:	108 lm/W
Rated power:	34.1 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000K K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	19



Physical details

Finish:	Grey
Length:	1977 mm
Width:	54 mm
Height:	85 mm
IP Rating:	IP20

lightworks

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes.
© 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.

RIDI GROUP UK