# iline 6 RIDI GROUP UK

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

## Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-WS-1198-830M-DADI-MP-FBES 97-IL600002ES Pendant Pendant Office, General and Retail

#### Specification text

Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 3618.1lm with an efficacy of 125lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1198 x W60 x H80mm. Finished in Black.





## Lighting performance

Output lumens:	3618.1 lm
Efficacy:	125 lm/W
Rated power:	29 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<19

### Physical details

Finish:	Black
Length:	1198 mm
Width:	60 mm
Height:	80 mm
IP Rating:	IP20







**RIDI** GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.