# iline 6 RIDI GROUP UK

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK


SALES@RIDI.CO.UK

## Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-S-1198-840M-DAD-OP-FG 97-IL600054 Surface Mount Surface Office, General and Retail

### **Specification text**

Surface Mount luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 2670Im with an efficacy of 127Im/W. Light source colour temperature 4000K and CRI 85. Complete with DALI control gear. Nominal dimensions L1198 x W60 x H80mm. Finished in Grey.




## Lighting performance

Output lumens:	2670 lm
Efficacy:	127 lm/W
Rated power:	21 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<22

#### Physical details

Finish:	Grey
Length:	1198 mm
Width:	60 mm
Height:	80 mm
IP Rating:	IP20







**RIDI** GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.