

- +44 (0) 1279 450882
- ⊕ WWW.RIDI-GROUP.CO.UK
- SALES@RIDI.CO.UK

Luminaire type

Product reference: IL6-WS-1478-830M-DADI-MP-FGED

Article Number: 97-IL600203ED
Product type: Pendant

Mounting type: Pendant
Applications: Office, General and Retail

Specification text


Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 4559lm with an efficacy of 125lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1478 x W60 x H80mm. Finished in Grey.



Lighting performance

Output lumens: 4559 lm 125 lm/W Efficacy: Rated power: 46.5 W Control gear: DALI Dimming range: 1-100% DC Suitable: Yes 3000 K Colour temperature: MacAdams < 3 CRI: 85 Radiation pattern: Symmetrical

Radiation pattern: Symmetric
Beam angle: Wide
Unified glare rating (U.G.R): <19



Physical details

 Finish:
 Grey

 Length:
 1478 mm

 Width:
 60 mm

 Height:
 80 mm

 IP Rating:
 IP20

