


### Luminaire type

|                    |                               |
|--------------------|-------------------------------|
| Product reference: | IL6-WS-1478-830M-DADI-MP-FGES |
| Article Number:    | 97-IL600203ES                 |
| Product type:      | Pendant                       |
| Mounting type:     | Pendant                       |
| Applications:      | Office, General and Retail    |


### Specification text

Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 4559lm with an efficacy of 125lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1478 x W60 x H80mm. Finished in Grey.



### Lighting performance

|                                |             |
|--------------------------------|-------------|
| Output lumens:                 | 4559 lm     |
| Efficacy:                      | 125 lm/W    |
| Rated power:                   | 46.5 W      |
| Control gear:                  | DALI        |
| Dimming range:                 | 1-100%      |
| DC Suitable:                   | Yes         |
| Colour temperature:            | 3000 K      |
| MacAdams                       | < 3         |
| CRI:                           | 85          |
| Radiation pattern:             | Symmetrical |
| Beam angle:                    | Wide        |
| Unified glare rating (U.G.R.): | <19         |



### Physical details

|            |         |
|------------|---------|
| Finish:    | Grey    |
| Length:    | 1478 mm |
| Width:     | 60 mm   |
| Height:    | 80 mm   |
| IP Rating: | IP20    |

