iline 6 RIDI GROUP UK

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-WS-1478-840M-DADI-OP-FGE 97-IL600218E Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 4959Im with an efficacy of 136Im/W. Light source colour temperature 4000K and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1478 x W60 x H80mm. Finished in Grey.





Lighting performance

Output lumens:	4959 lm
Efficacy:	136 lm/W
Rated power:	46.5 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	4000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<22

Physical details

Finish:	Grey
Length:	1478 mm
Width:	60 mm
Height:	80 mm
IP Rating:	IP20







RIDI GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.