iline 6 RIDI GROUP UK

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-WS-1478-830M-DAD-OP-FG 97-IL600230 Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 3199.06lm with an efficacy of 123lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear. Nominal dimensions L1478 x W60 x H80mm. Finished in Grey.





Lighting performance

3199.06 lm
123 lm/W
23 W
DALI
1-100%
Yes
3000 K
< 3
85
Symmetrical
Wide
<22

Physical details

Finish:	Grey
Length:	1478 mm
Width:	60 mm
Height:	80 mm
IP Rating:	IP20





lightworks

RIDI GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.