

Luminaire type

| | |
|--------------------|----------------------------|
| Product reference: | IL6-S-1478-830M-DAD-OP-FG |
| Article Number: | 97-IL600248 |
| Product type: | Surface Mount |
| Mounting type: | Surface |
| Applications: | Office, General and Retail |

Specification text

Surface Mount luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 3199.06lm with an efficacy of 123lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear. Nominal dimensions L1478 x W60 x H80mm. Finished in Grey.



Lighting performance

| | |
|--------------------------------|-------------|
| Output lumens: | 3199.06 lm |
| Efficacy: | 123 lm/W |
| Rated power: | 23 W |
| Control gear: | DALI |
| Dimming range: | 1-100% |
| DC Suitable: | Yes |
| Colour temperature: | 3000 K |
| MacAdams | < 3 |
| CRI: | 85 |
| Radiation pattern: | Symmetrical |
| Beam angle: | Wide |
| Unified glare rating (U.G.R.): | <22 |



Physical details

| | |
|------------|---------|
| Finish: | Grey |
| Length: | 1478 mm |
| Width: | 60 mm |
| Height: | 80 mm |
| IP Rating: | IP20 |

