# iline 6 RIDI GROUP UK

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

## Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-R-1494-840M-DAD-OP-FGED 97-IL600331ED Recessed Recessed Office, General and Retail

#### Specification text

Recessed luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 3298lm with an efficacy of 127lm/W. Light source colour temperature 4000K and CRI 85. Complete with DALI control gear and DALI test 3hr emergency. Nominal dimensions L1494 x W76 x H76.5mm. Finished in Grey.




### Lighting performance

| 3298 lm     |
|-------------|
| 127 lm/W    |
| 0 W         |
| DALI        |
| 1-100%      |
| Yes         |
| 4000 K      |
| < 3         |
| 85          |
| Symmetrical |
| Wide        |
| <22         |
|             |

#### Physical details

| Finish:    | Grey    |
|------------|---------|
| Length:    | 1494 mm |
| Width:     | 76 mm   |
| Height:    | 76.5 mm |
| IP Rating: | IP20    |
|            |         |





lightworks

**RIDI** GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.