iline 6 RIDI GROUP UK

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-WS-1968-840M-DAD-MP-FGE 97-IL600427E Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 40521m with an efficacy of 1171m/W. Light source colour temperature 4000K and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1968 x W60 x H80mm. Finished in Grey.





Lighting performance

| Output lumens: | 4052 lm |
|-------------------------------|-------------|
| Efficacy: | 117 lm/W |
| Rated power: | 30.6 W |
| Control gear: | DALI |
| Dimming range: | 1-100% |
| DC Suitable: | Yes |
| Colour temperature: | 4000 K |
| MacAdams | < 3 |
| CRI: | 85 |
| Radiation pattern: | Symmetrical |
| Beam angle: | Wide |
| Unified glare rating (U.G.R): | <19 |

Physical details

| Finish: | Grey |
|------------|---------|
| Length: | 1968 mm |
| Width: | 60 mm |
| Height: | 80 mm |
| IP Rating: | IP20 |
| | |





lightworks

RIDI GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.