iline 6 RIDI GROUP UK

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK


SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-WS-1968-830M-DAD-OP-FBE 97-IL600429E Pendant Pendant Office, General and Retail

Specification text

Pendant luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 4265.09Im with an efficacy of 123Im/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and manual test 3hr emergency. Nominal dimensions L1968 x W60 x H80mm. Finished in Black.





Lighting performance

Output lumens:	4265.09 lm
Efficacy:	123 lm/W
Rated power:	30.6 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<22

Physical details

Finish:	Black
Length:	1968 mm
Width:	60 mm
Height:	80 mm
IP Rating:	IP20





The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 50P.

lightworks