## iline 6 RIDI GROUP UK

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK


SALES@RIDI.CO.UK

### Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-S-1968-830M-DAD-OP-FW 97-IL600446 Surface Mount Surface Office, General and Retail

#### Specification text

Surface Mount luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 4265.09Im with an efficacy of 123Im/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear. Nominal dimensions L1968 x W60 x H80mm. Finished in White.




#### Lighting performance

Output lumens:	4265.09 lm
Efficacy:	123 lm/W
Rated power:	30.6 W
Control gear:	DALI
Dimming range:	1-100%
DC Suitable:	Yes
Colour temperature:	3000 K
MacAdams	< 3
CRI:	85
Radiation pattern:	Symmetrical
Beam angle:	Wide
Unified glare rating (U.G.R):	<22

#### Physical details

Finish:	White
Length:	1968 mm
Width:	60 mm
Height:	80 mm
IP Rating:	IP20





# lightworks

**RIDI** GROUP UK

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.