iline 6 RIDI GROUP UK

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications: IL6-R-1984-830M-DAD-MP-FGES 97-IL600522ES Recessed Recessed Office, General and Retail

Specification text

Recessed luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <19. Light output of 3930.44lm with an efficacy of 114lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1984 x W76 x H76.5mm. Finished in Grey.




Lighting performance

3930.44 lm
114 lm/W
0 W
DALI
1-100%
Yes
3000 K
< 3
85
Symmetrical
Wide
<19

Physical details

Finish:	Grey
Length:	1984 mm
Width:	76 mm
Height:	76.5 mm
IP Rating:	IP20





lightworks

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.

RIDI GROUP UK