iline 6 **RIDI** GROUP UK

+44 (0) 1279 450882

WWW.RIDI-GROUP.CO.UK

SALES@RIDI.CO.UK

Luminaire type

Product reference: Article Number: Product type: Mounting type: Applications:

IL6-R-1984-830M-DAD-OP-FGES 97-IL600528ES Recessed Recessed Office, General and Retail

Specification text

Recessed luminaire from the iline 6 family. Symmetrical, Wide lighting distribution, UGR <22. Light output of 4265.09lm with an efficacy of 123lm/W. Light source colour temperature 3000K and CRI 85. Complete with DALI control gear and self test 3hr emergency. Nominal dimensions L1984 x W76 x H76.5mm. Finished in Grey.




Lighting performance

| Output lumens: | 4265.09 lm |
|-------------------------------|-------------|
| Efficacy: | 123 lm/W |
| Rated power: | 0 W 0 |
| Control gear: | DALI |
| Dimming range: | 1-100% |
| DC Suitable: | Yes |
| Colour temperature: | 3000 K |
| MacAdams | < 3 |
| CRI: | 85 |
| Radiation pattern: | Symmetrical |
| Beam angle: | Wide |
| Unified glare rating (U.G.R): | <22 |
| | |

Physical details

| Finish: | Grey |
|------------|---------|
| Length: | 1984 mm |
| Width: | 76 mm |
| Height: | 76.5 mm |
| IP Rating: | IP20 |
| | |





lightworks

The details provided in this data sheet were prepared with due care but are still subject to error. We retain the right to make formal, technical and pricing changes. © 22/01/25 RIDI Lighting Ltd, Units 8 & 9 The Marshgate Centre, Harlow Business Park, Parkway, Harlow, Essex, CM19 5QP.

RIDI GROUP UK